

Certificate of Conformance to Requirements for Welding Electrode

Product Type: HOBART 447A

Classification: **E6013**

Specifications: AWS A5.1/A5.1M; ASME SFA 5.1

Polarity

0.39

0.36

0.08

Diameter Tested: 5/32"

 Date Tested:
 7/20/2023

 Date Generated:
 8/21/2023

This is to certify that the product named above and supplied on the referenced order number is of the same classification, manufacturing process, and material requirements as the material which was used for the test that was concluded on the date shown, the results of which are shown below. All tests required by the specifications shown for classification were performed at that time and the material tested met all requirements. It was manufactured and supplied by the Quality System Program of Hobart Brothers, which meets the requirements of ISO 9001, ANSI/AWS A5.01, and other specification and Military requirements, as applicable. This document supplies actual test results of non-specific inspection in conformance with the requirements of EN 10204, type 2.2 certification.

MADE IN THE U.S. OF U.S. AND IMPORTED MATERIALS.

Size

5/32X14 in / AC / PE6592

Test	Settings
	Amps

Volts

Preheat F(C)

Interpass F(C)

5/32X14 in			DCEN							145		25					225F ()					350F ()							
5/32X14 in			AC					150					23					225F ()				300F (
Mechanical Properties - Tensile																													
Size / Polarity	Ref. No	э.	Testing Conditions				Ult	Ult. Tensile Strength psi(MPa)						Yield Strength psi(MPa)						Elong.% in 2"									
5/32X14 in / DCEN	PE644	9	Aged 48 Hrs 220F					76,000 (521)						67,000 (461)					\top	25									
5/32X14 in / AC	PE659	2	Aged 48 Hrs 220F					73,000 (505)						64,000 (438)						25									
Size / Polarity	Ref. No).	Radiograph					Fillet We											d Test										
5/32X14 in / DCEN	PE644	9 Co	Conforms					Horizontal :						Overhead : Conforms						S Vertical : Conforms									
5/32X14 in / AC	PE659	2 Co	Conforms					Horizontal :						Overhead : Conforms						Vertical : Conforms									
	Chemical Analysis																												
Size / Polarity	/ Ref. No.		С	Mn	Р	s	Si	Cu	Cr	V	Ni	Мо	ΑI	Ti	Nb	Со	В	W	Sn	Fe	Sb	N	Mg	Zn	Ве	Sb	As		
5/32X14 in / DC	EN / PE644	.9	0.06	0.32	Г	П	0.30		0.04	0.01	0.04	0.01	П	П			П	ГΠ				ГП					\Box		

0.01

0.04

0.04

0.01

James a Oneund

James A. Owens, Q.A. Specialist

Certification and Limited Warranty - Data for the above supplied product are those obtained when welded and tested in accordance with the above specification. All tests for the above classification were satisfied. Other tests and procedures may produce different results.